



Science Equip
Better Products For Laboratory & Industry



www.science-equip.co.uk

UNDER-COUNTER LABORATORY FRIDGE SOLID DOOR 151L WHITE



SKU CODE:	PRODUCT CODE:	DESCRIPTION:
444440964	LSR151UK	Under-counter Laboratory Fridge Solid Door 151L White



+2°C to +10°C Operating Temperature Range

Desired temperature can be set by the user

NEW Advanced Controller

Records temperature accurate to 0.1°C

NEW Unique Anti Microbial Handle

Helps prevent the growth of bacteria and minimise the potential for cross contamination

Fitted Lock as Standard

Maintains security and ensures the unit can only be accessed by approved personnel

Fitted Rollers

For ease of movement

Wire Shelves and Baskets

Enables optimum air flow inside unit

Audible Warning Alarms

Alerts user should internal temperature deviate from set parameters



FULL SPECIFICATION - LSR151UK UNDER-COUNTER
LABORATORY FRIDGE SOLID DOOR 151L WHITE

Description	Under-counter
SKU Code	444440964
EAN Code	5052263009646
GDPA Code	LSR151UK
Gross Capacity (L)	151
Net Capacity (L)	145
Unit External Width (mm)	595
Unit External Depth (mm)	595
Unit External Height (mm)	845
Product Weight (kg)	36
Packed Width (mm)	657
Packed Depth (mm)	694
Packed Height (mm)	884
Packed Weight (kg)	40
Country of Origin	UK
Internal Dimensions (mm) (WxDxH)	500 x 450 x 705 (step: 165d x 185h)
External Finish	White
Internal Finish	White
Type of Plastic	SRL800 (HIPS/ABS Mix)
Temperature Range	+2°C to +10°C
Colour	White/Green
Door Type	Solid
Door Style	Hinged, Reversible
Door Open Depth (mm)	1165
Replacement Door Seal	No
Open Door Sensor	Yes
Lock	Yes
Adjustable Feet	2 Adjustable Feet, 2 Rear Rollers
Temperature Display on Panel	Yes
Temperature Alarm	Yes
Number of Shelves	3
Number of Shelf Positions	6
Shelf Size	3: 320 x 520 x 6
Shelf Material	Wire
Moulded Drawers	0
Adjustable Door Bins	2 Wire
Interior Light	No
Fan	No
Spark Free	Yes
Auto or Manual defrost	Automatic
Controller Type	Digital, External
Climate Class	SN
Refrigerant Type	R600a
CFC Free	Yes
HFC Free	Yes
HCFC Free	Yes
UK 3 Pin Plug	Yes
Other Plug Types Available	Yes
Voltage Supply	230
Aux Output	No
Insulation Thickness (mm)	45
Insulation Type	Cyclopentane
Anti Microbial Handle	Yes